



عمران مدرن  
بازار نوین ارتباطات ساختمانی

# نصب آسانسور و تهیه کلیه قطعات

سراسر کشور



با قیمت استثنایی و اکیپ متخصص

برای مشاوره رایگان تماس بگیرید

02162999675

# Combi32 - 5.5kW - AC2

Ref.:

INSTALLATION	GIVEN	SUPPOSED
Type of roping	1 : 1	
Car speed [m/s]	1	
Duty load [Kg]		
Car weight [Kg]		
Ropes n° x diameter [mm]	5 x 10	
Angle groove [°]	V / 35	
Angle undercut groove [°]	90	
Car travel [m]		
Ropes weight [Kg]		
Counterweight [Kg]		
Counterweight [%]		
Comp. chains weight [Kg]		
Comp. chains weight [%]		
Out of balance load [Kg]		
Static load [kg]		
Shaft efficiency [%]		80
Machine	Above	
Divertors on bearings nr		
Divertors on bushing nr		
Minimum alfa angle [°]		
Regulation	4/16 AC2	
Tropicalization	NO	
Voltage [V]	380	
Ropes tensile strength [kg]		
Type of ropes	Fiber core	
<b>Material not included in price</b>		
Flat / High frame		
Distance between ropes [mm]		0
Vibration dampers	NO	
Divertors Ø [mm]		
Divertor protection		
Extended shaft	NO	
Centre gear-sheave [mm]		
Centre gear-bearing [mm]		
Static load [Kg]		

GEAR / MOTOR		Price-List €
<b>GEAR</b>	Combi32	
Quantity n°	1	
Traction sheave position	to be defined	
Ratio	1/37	
Traction sheave diameter [mm]	480	
Ropes n° x diameter [mm]	5 x 10	
Angle groove [°]	V / 35	
Angle undercut groove [°]	90	
Pitch of grooves [mm]	16	
Drum Brake voltage DC [V]	220	
Flywheel		
MAX. static load [kg]	2800	
MAX. out of balance load [kg]		
Traction sheave speed [m/s]	1	
<b>MOTOR</b>	MGT	
Frame size		
Poles / Regulation	4/16 AC2	
Power [kW syncr.]	5.5	
Voltage [V]	380	
Rated frequency [Hz]	50	
Rated current [A]	11	
Acceleration current [A]	32	
Thermistors	3	
Sts./h. - ED%	180 40	
Power [kW asyncr.]	5.5	
Adjusting frequency [Hz/RPM]	51,99	
Full load current [A]		
<b>ACCESSORIES</b>	<b>Q.ty</b>	
Ropes protection	1	
Packing	1	