



عمران مدرن
بازار نوین ارتباطات ساختمانی

نصب آسانسور و تهیه کلیه قطعات

سراسر کشور



با قیمت استثنایی و اکیپ متخصص

برای مشاوره رایگان تماس بگیرید

02162999675



Offer


Ref.: **NEW ORDER - REV1 Installation :ITEM 2**

Offer N° : **FT** of

| INSTALLATION | GIVEN | SUPPOSED |
|---------------------------------------|------------|----------|
| Type of roping | 1 : 1 | |
| Car speed [m/s] | | 1,06 |
| Duty load [Kg] | | |
| Car weight [Kg] | | |
| Ropes n° x diameter [mm] | 5 x 10 | |
| Angle groove [°] | V / 35 | |
| Angle undercut groove [°] | 97 | |
| Car travel [m] | | |
| Ropes weight [Kg] | | |
| Counterweight [Kg] | | |
| Counterweight [%] | | |
| Comp. chains weight [Kg] | | |
| Comp. chains weight [%] | | |
| Out of balance load [Kg] | | |
| Static load [kg] | | |
| Shaft efficiency [%] | | 80 |
| Machine | Above | |
| Divertors on bearings nr | | |
| Divertors on bushing nr | | |
| Minimum alfa angle [°] | | |
| Regulation | 4/00VVVF | |
| Tropicalization | NO | |
| Voltage [V] | 380 | |
| Ropes tensile strength [kg] | | |
| Type of ropes | Fiber core | |
| Material not included in price | | |
| Flat / High frame | | |
| Distance between ropes [mm] | | 0 |
| Vibration dampers | NO | |
| Divertors Ø [mm] | | |
| Divertor protection | | |
| Extended shaft | NO | |
| Centre gear-sheave [mm] | | |
| Centre gear-bearing [mm] | | |
| Static load [Kg] | | |
| | | |
| | | |
| | | |

| GEAR / MOTOR | | Price-List € |
|-------------------------------|---------------|--------------|
| GEAR | LEO | |
| Quantity n° | 1 | |
| Traction sheave position | to be defined | |
| Ratio | 2/71 | |
| Traction sheave diameter [mm] | 450 | |
| Ropes n° x diameter [mm] | 5 x 10 | |
| Angle groove [°] | V / 35 | |
| Angle undercut groove [°] | 97 | |
| Pitch of grooves [mm] | 17 | |
| Drum Brake voltage DC [V] | 220 | |
| Flywheel | 350-28P | |
| MAX. static load [kg] | 3000 | |
| MAX. out of balance load [kg] | 428 | |
| Traction sheave speed [m/s] | 1,06 | |
| MOTOR | SASSI | |
| Frame size | 240118A | |
| Poles / Regulation | 4/00VVVF | |
| Power [kW syncr.] | 7,30 | |
| Voltage [V] | 380 | |
| Rated frequency [Hz] | 50 | |
| Rated current [A] | 17,40 | |
| Acceleration current [A] | 34,80 | |
| Thermistors | 3 | |
| Sts./h. - ED% | 240 40 | |
| Power [kW asynchr.] | 7,30 | |
| Adjusting frequency [Hz/RPM] | 49,91 / 1.497 | |
| Full load current [A] | | |
| ACCESSORIES | Q.ty | |
| Ropes protection | 1 | |
| Packing | 1 | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

- Payment
- Goods delivered
- Packing
- Offer valid through


Delivery time

| | Net € | Price-List € |
|--------------------|-------|--------------|
| Unit price | | |
| Total price | | |

